



Equipment

Designation	Technology	Nozzle size	Fluid output	Max fan width at 20cm (8in)	Part number
Gun FStart G HVLP-15-Mva	HVLP	1.5	165 cc/mn (5.6 oz/mn)	M: 20 - 30 cm (7.9 - 11.8 in)	135756115
Gun FStart G HVLP-18-Mva	HVLP	1.8	220 cc/mn (7.4 oz/mn)	M: 20 - 30 cm (7.9 - 11.8 in)	135756118
Gun FStart G HVLP-22-Mva	HVLP	2.2	280 cc/mn (9.5 oz/mn)	M: 20 - 30 cm (7.9 - 11.8 in)	135756122
Gun FStart G CONV-15-Lva	CONV	1.5	165 cc/mn (5.6 oz/mn)	L: 30 - 40 cm (11.8 - 15.7 in)	135756215
Gun FStart G CONV-18-Lva	CONV	1.8	220 cc/mn (7.4 oz/mn)	L: 30 - 40 cm (11.8 - 15.7 in)	135756218
Gun FStart G CONV-22-Lva	CONV	2.2	280 cc/mn (9.5 oz/mn)	L: 30 - 40 cm (11.8 - 15.7 in)	135756222

Accessories

Designation	Part number
Gravity Plastic cup for FStart	129756928

Kits

Designation	Gun	Hoses dimensions	Part number
Pack Airspray Lucky "FStart G HVLP + air hose"	FStart G HVLP-18-Mva	7.5m Air - ID8mm	152756280
Pack Airspray Lucky "FStart G CONV + air hose"	FStart G CONV-18-Lva	7.5m Air - ID6.5mm	152756380

Spare Parts

Designation	Part number
Maintenance kit for FStart G	129756901
Nozzle + Needle FStart HVLP-15	131756115
Nozzle + Needle FStart HVLP-18	131756118
Nozzle + Needle FStart HVLP-22	131756122
Aircap FStart G HVLP-1522-Mva	132756110
Aircap FStart G CONV-1518-Lva	132756210
Aircap FStart G CONV-22-Lva	132756220
Nozzle + Needle FStart CONV-22	131756222
Nozzle + Needle FStart CONV-18	131756218
Nozzle + Needle FStart CONV-15	131756215




FStart G

Gravity Airspray Spray Gun

Airspray / Manual Guns



JOB IS DONE!

-  **Good value for money**
-  **Comfortable spray gun**
-  **Easy to repair**



Markets



FStart G

Gravity Airspray Spray Gun

Multi-purpose entry price level spray gun, the FStart G is easy to use and guarantees a high-quality finish.



HVLP



Airspray Conventional

SAMES KREMLIN's FStart G spray guns make it easy and cost-effective to apply water-based or solvent-based coatings.

HVLP and Conventional sprayers are available to meet the needs of small to large finishing shops. The FStart G spray guns can be used by both beginners and experienced professionals giving a desired high-quality finish.

The FStart spray guns are the result of 95 years of experience in Airspray technology. On top of being an economical cost solution, this new Airspray gun has a comfortable and ergonomic design and is one of the lightest guns in its class.



Technical data table

Designation	Value	Unit: metric (US)
Maximum Fluid Pressure	6 (87)	bar (psi)
Maximum Air Pressure	6 (87)	bar (psi)
Maximum Fluid Temperature	50 (122)	°C (°F)
Air Inlet	M 1/4" NPS	
Stainless Steel, Aluminum Wetted Parts	♦	
Recommended CONV Air Pressure	2.5 (36) – 3.5 (51)	bar (psi)
Recommended HVLP/LVLP Air Pressure	1.5 (22) – 2.5 (36)	bar (psi)
Air Consumption CONV (at 2.5 - 3.5 bar / at 36 - 51 psi)	23.3 (13.7)	m3/h (cfm)
Air Consumption HVLP/LVLP (at 1.5 - 2.5 bar / at 22 - 36 psi)	20.4 (12)	m3/h (cfm)
Trigger Pull	16 (3.6)	N (lbs)
Tank Capacity	0.6 (0.16)	l (gal)
Weight	410 (14.5)	g (oz)

PERFORMANCE

- 1 Fine adjustments to achieve the perfect spray pattern for all applications
 - ♦ SAMES KREMLIN finishing quality at entry price level
 - ♦ SAMES KREMLIN's experience in Airspray since 1924

PRODUCTIVITY

- 2 "Fine atomization" aircap adjustable to 360 degrees
- 3 Soft springs for a responsive and reduced trigger pull
- 3 New trigger design for more comfort
- 4 One of the lightest manual spray guns in its category ensuring a reduction of carpal tunnel injuries

SUSTAINABILITY

- 5 Aluminum body for easy cleaning
 - ♦ A small investment for long-term use: Only one maintenance kit for reduced inventory



Description

