Bond | Protect | Beautify

www.sames-kremlin.com



Equipment

Designation	Technology	Nozzle size	Fluid output	Max fan width at 20cm (8in)	Part number
Gun FStart S CONV-15-Mva	CONV	1.5	260 cc/mn (8.8 oz/mn)	M: 20 - 30 cm (7.9 - 11.8 in)	135756515
Gun FStart S CONV-18-Mva	CONV	1.8	290 cc/min (9.8 oz/min)	M: 20 - 30 cm (7.9 - 11.8 in)	135756518

Accessories

Designation	Capacity	Part number
Aluminum suction cup	1L	138400000

Spare Parts

Designation	Details Part number
Maintenance kit for FStart P/S	129756902
Nozzle + Needle FStart CONV-15	131756215
Nozzle + Needle FStart CONV-18	131756218
Aircap FStart S CONV-1518-Mva	132756510



FStart S

Suction Airspray Spray Gun


Airspray / Manual Guns



JOB IS DONE!

- Good value for money
- Comfortable spray gun
- Easy to repair















www.sames-kremlin.com



38243 MEYLAN Cedex - FRANCE Phone: +33 (0)476416060 - Fax: +33 (0)476416090

13 chemin de Malacher - CS 70086



FStart S

SAMES 5 KREMLIN

Suction Airspray Spray Gun

The FStart S suction-fed conventional spray gun is the right solution for hard to atomize coatings at an entry level price.







PERFORMANCE



Description

- 1 Fine adjustments to achieve the perfect spray pattern for all applications
- ♦ SAMES KREMLIN finishing quality at entry price level
- ♦ SAMES KREMLIN's experience in Airspray since 1924

PRODUCTIVITY

- 2 "Fine atomization" aircap adjustable to 360°
- 3 Soft springs for a responsive and reduced trigger pull
- 3 New trigger design for more comfort
- 4 One of the lightest manual spray guns in its category ensuring a reduction of carpal tunnel injuries

SUSTAINABILITY

- 4 Aluminum body for easy cleaning
- **5** Reusable aluminum cup with a simplified locking system
- ♦ A small investment for long term use: Only one maintenance kit for reduced inventory



SAMES KREMLIN's FStart S spray guns make it easy and cost-effective to apply water-based or solvent-based coatings.

Conventional sprayers are available to meet the needs of small to large finishing shops. The FStart S spray guns can be used by both beginners and experienced professionals giving a desired high quality finish.

The FStart spray guns are the result of 95 years of experience in Airspray technology. In addition to being an economical solution, this new Airspray gun has a comfortable and ergonomic design and is one of the lightest guns in its class.



Designation	Value	Unit: metric (US)
Maximum Fluid Pressure	6 (87)	bar (psi)
Maximum Air Pressure	6 (87)	bar (psi)
Maximum Fluid Temperature	50 (122)	°C (°F)
Air Inlet	M 1/4" NPS	
Fluid Inlet	M 3/8" NPS	
Stainless Steel, Aluminum Wetted Parts	•	
Recommended CONV Air Pressure	2.5 (36) – 3.5 (51)	bar (psi)
Air Consumption CONV (at 2.5 - 3.5 bar / at 36 - 51 psi)	21.3 (12.5)	m3/h (cfm)
Trigger Pull	16 (3.6)	N (lbs)
Tank Capacity	1 (0.26)	l (gal)
Weight	402 (14.2)	g (oz)

Bond | Protect | Beautify